






Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light with 62° beam angle facing up and down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø7mm, spacing 100x80mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module, power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	5,1kg / 5,1kg
Box dimensions [cm]	22,5x19,5x32

Technical data

4 LED modules.	Cree Jx3030 3000K no.1805004
Driver	Philips Xitanium 20W/m 0.15-0,5A 54V 230V 12NC
Light source wattage	17,6W
Luminaire wattage	22,2W
Lamp luminous flux	2444lm
Luminaire luminous flux	1115,6lm
Light source efficiency	138,9lm/W
Efficiency of the luminaire	50,3lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF >0,95
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A**

Inrush current	4,4A / 66µs
----------------	-------------

Spare parts

46999560	LED module.
46999747	Power supply.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
1952AL	ALUMINIUM	9006
1952GR	GRAPHITE	7016